

DWG NO.
C-100072

TOP-LINK

mechanical demands: $+0.40_{-0.20}^{\text{N}}$ with 1.8mm stroke.
Spring force: Min 1.6
Full stroke: 2.7mm
Plating plunger: Min 0.40um Au over 1.5um Ni
Plating body: Min 0.1um Au over 1.4um .

Technical drawing of a mechanical part, showing two views: a top view and a side view.

Top View: The part is rectangular with a central slot and two side slots. The overall width is 5.0 . The overall length is 7.8 ± 0.20 .

Side View: The part has a central slot and two side slots. The overall height is 4.6 . The width of the central slot is 0.80 .

DIMENSIONS IN MM TOLERANCES UNLESS OTHER SPECIFIED				MATL		HT TR		FIN			
0 = ±				DVN		APVD		Top-Link Electronics Ltd.			
0.0 = ±0.15				Benny							
0.00 = ±0.10				CHK		REL					
0.000 = ±											
ANGLE: ±1°											
SURF TEXTURE: 3.2/√				NAME BATTERY CONNECTOR 2 POS.							
REMOVE BURRS, BREAK SHARP EDGES R0.05 MAX				PGC-15-10.0-R-2P-5.08PH							
DO NOT SCALE PRINT		SCALE 1:1		A4		DWG NO. C-100072		SHEET 1 OF 1		REV B	

		100072-2	
		PART NUMBER	
MATL	HT TR	FIN	
DWN	APVD	✓	
Benny		Top-Link Electronics Ltd.	
CHK	REL		
NAME BATTERY CONNECTOR 2 POS. PGC-15-10.0-R-2P-5.08PH			
SCALE	DWG	SHEET	REV
1:1	A4 ND C-100072	1 OF 1	B

USED ON