








THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TOP-LINK WITHOUT WRITTEN AUTHORIZATION FROM TOP-LINK ELECTRONICS FACTORY



DWG NO.
C-100576



Recommended PCB Layout



USED ON

TOP-LINK

Notes:
1) Material(材质):
Housing: PA 4,6 (30% Glass Filled)Color Black. (UL94V-0)
Contact: Brass
Spring : Stainless steel wire

2) Plating:

1) Body: Min 0.1um Gold plating over min. 1.4um Nickel plating
(Body: 镀金0.1um Min 镍底1.4um Min)
2) Plunger: Min 0.4um Gold plating over min. 1.4um Nickel plating
(Plunger: 镀金0.4um Min 镍底1.4um Min)

3) Mechanical:

Total stroke(总行程): 1.70mm
Durability(寿命): 10,000 cycle min.

4) Electrical(电性能)

Contact resistance(接触阻抗): 30mOhm Max.
Voltage rating(额定电压): 36V DC Max
Current rating(额定电流): 2.0A

DIMENSIONS IN MM
TOLERANCES UNLESS
OTHER SPECIFIED

0 = ±
0.0 = ±0.15
0.00 = ±0.10
0.000 = ±
ANGLE: ±1°

SURF TEXTURE: 32/
REMOVE BURRS, BREAK
SHARP EDGES R0.05 MAX
DO NOT SCALE PRINT

MATL

HT TR

FIN

DWN
QIN

APVD

REL

Top-Link
Electronics Ltd.

NAME BATTERY CONNECTOR 2 POS.

SCALE 1:1 A4 DWG C-100576

SHEET 1 OF 1 REV A

4

3

2

1