


proposal



TOP-LINK

Notes:

- 1 Dimensions shall be interpreted per ASME Y14.5M.
- 2 Mechanical performance(See the table 1)
- 2.1>The force is the average of forces obtained when plunger goes downwards and upwards.
- 2.2>Warning:Working height are not permitted to be less than Min working height.
- 3 Electrical performance
Resistance: 30mOhm Max.
Current rating: 2.0A
- 4 RoHS compliant.

Table 1 Mechanical performance

Working height	4.00mm	120±30gf <2.1>
Durability	10000cycle	

Item	Part name	Qty/Ed	Material	Finish
1	Body	1	Leaded Brass	Au 0.1um plating Ni 1.4um
2	Plunger	1	Leaded Brass	Au 0.4um plating Ni 1.4um
3	Spring	1	Stainless steel wire	_____
4				
5				

Top-Link Electronics Ltd.		Type	Customer drawing	Unit	mm	Weight	_____				
TOLERANCES UNLESS OTHER SPECIFIED		DWN:	Cai wanlu	APVD:							
0.0 = ±0.15		CHK:		REL:							
0.00 = ±0.10		POGO PIN					Top-Link Electronics Ltd.				
0.000 = ±0.05											
SURF. TEXTURE:											
REMOVE SHARP EDGES											
BREAK SHARP EDGES		Scale	1:1	Size	A4	DWG No.	C-101100	Page	1/1	Rev.	A1
SCALE PRINT.											

101100-1
PART NUMBER

A1	Update	2015/12/26
A	NEW	2007/09/02
Rev.	Revision record.	Date.