



THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TOP-LINK PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TOP-LINK LTD.



DWG NO.
101460

USED ON

-



Notes:

△Material(材质):

- 1)Body : Brass
- 2)Plunger : Brass
- 3)Spring : stainless steel wire

- 1)Body: Min. 0.1um Gold plating over min. 1.4um Nickel plating (Body: 镀0.1um Min 镍底1.4um Min)
- 2)Plunger: Min 0.4um Gold plating over min. 1.4um Nickel plating (Plunger: 镀0.4um Min 镍底1.4um Min)

3 Mechanical(机械性能):

- 1)Force: 80±3.5gf per pin at 1.5mm stroke (力: 下压1.5mm的力: 80±35gf)
- 2)Total stroke(总行程) : 1.90mm
- 3)Durability(寿命): 10,000 cycle min.
- 4 Electric(电性能)

TOP LINK

- 1)Contact resistance(接触阻抗): 30mOhm Max.
- 2)Voltage rating(额定电压): 36V DC Max
- 3)Current rating(额定电流): 2.0A

LDC	-
DIST	-

NEW		2010/10/21
REVISION		
RECORD		
APVD		
DATE		

DIMENSIONS IN MM				TOLERANCES UNLESS OTHER SPECIFIED			
0	= ±-			0.0	= ±0.15		
0.00	= ±0.10			0.000	= ±-		
ANGLE: ±1°							
SURF TEXTURE: 32/							
REMOVE BURRS, BREAK SHARP EDGES R0.05 MAX							
DD NOT SCALE PRINT							
MATL	△	HT TR	-	FIN	-	△	
DWN	Qin	APVD					
CHK		REL					
NAME	PGGD PIN PG-2.0-0.5-1.5-5.0-7.0						
SCALE	1:1	A4	DWG	NO.	C-101460	SHEET	1 OF 1
						REV	A

Top-Link
Electronics Ltd.

PART NUMBER

101460-1