


proposal



TOP-LINK

Item	Part name	Q'ty/Ed	Material	Finish
1	Body	1	Leaded Brass	Au 0.10um plating Ni 1.4um
2	Plunger	1	Leaded Brass	Au 0.40um plating Ni 1.4um
3	Spring	1	Stainless steel wire	
4				
5				

Table 1 Mechanical performance		
working height	3.20mm	100±30gf <2.1>
Durability	10000cycle	

Notes:

- 1 Dimensions shall be interpreted per ASME Y14.5M.
- 2 Mechanical performance(See the table 1)
<2.1>The force is the average of forces obtained when plunger goes downwards and upwards.
<2.2>Warning: Working height are not permitted to be less than Min working height.
- 3 Electrical performance
Resistance: 30mOhm Max.
Current rating: 2.0A
- 4 RoHS compliant.

Top-Link Electronics Ltd.		Type	Customer drawing	Unit	Weight
TOLERANCES UNLESS OTHER SPECIFIED		DWN:	Cai wanlu	APVD:	
0.0 = ±0.15		CHK:		REL:	
0.00 = ±0.10		Name POGO PIN			
0.000 = ±		Scale 1:1			
SURF. TEXTURE:		Size A4			
REMOVE BURRS:		DWG No. C-20101011180			
BREAK SHARP EDGES		Page 1/1			
R0.05 MAX. DO NOT SCALE PRINT.		Rev. 1.1			

20101011180
PART NUMBER

DIST

1.1	Update	2015/05/15
1	NEW	2015/05/14
Rev.	Revision record.	Date.